



DISPLAY	
Display Dimension	34" diagonally
Panel	VA LCD
Brightness	400 nits HDR / 350 typical
Color Gamut	DCI-P3 90%
Contrast	10,000,000:1 DCR / 4,000:1 typical
Back-light	Edge-lit LED
Resolution	3440 x 1440 H/V
Aspect Ratio	21:9
Response Time	1ms MPRT / 7ms with OD Driver
Viewing Angle	178° H/V
Display Colors	8bit + FRC (16.7M)
Panel Frequency	165Hz @ 3440 x 1440 Resolution
HDR	VESA DisplayHDR400 certified
INTERFACES	
Interface Ports	1x DisplayPort 1.4 x1 (3440 x 1440 @165Hz, Bandwidth: 32.4 Gbps), 1x HDMI 2.1, 1x USB Type-C x1 (DP 1.4 Alt. Mode, USB 2.0 with 65watts PD, HDCP 2.2), 1x USB 3.2 Gen1 (A type), USB 3.2 Gen1 (B type), 1x 3.5mm audio
TOUCH	
Active Pen	Microsoft HLK certified; Pen Protocol 2.0
Multi-Touch	10-Point Simultaneous
OS Support	Windows / Mac OS / Android / Linux
PEN	
Features	4096 levels of pressure sensitivity, Magnetic pen holder, pen charge
MICROPHONE	
Type	Digital
Array 8 channel input	8 channel input
Audio Format	1 channel 48KHz, 16Bits PCM
Algorithm Support	Beamforming, Echo Cancellation, Noise Suppression, Reverberation, Cancellation
Effective Distance	Up to 7 meters
CAMERA	
Still Image Capture	RGB: 3840 x 2160 @30fps IR: 680*480 @15fps
Automatic Controls	Exposure, White Balance, Gain
Windows Hello	Yes
SOUND	
Speaker	12W x2
POWER	
Power Input	DC 24V 6.24A
Consumption On	55 W
Standby/Off	<=0.5W / <=0.3W
OPERATING CONDITION	
Operating Condition Temperature	0 - 40°C
Humidity/Storage Humidity	10 - 80% Non-condensing, 10 - 90% Non-condensing
Storage Temperature	-20 - 60°C
PHYSICAL CHARACTERISTICS	
Mounting Characteristics	VESA 100 x 100 mm
Unit Dimension	32.2" x 14.6" x 2.3" / 817.72mm x 371.77mm x 59.1mm
Package Dimension	965mm x 240mm x 490mm
Net Weight (including stand)	11.8 Kg
Gross Weight	16 Kg
Stand Tilt	5° Down 60° Up
Stand Swivel	45° Left or Right
ACCESSORIES	
Accessories	1x 1.5 meter power cable, 1x 2 meter power adapter, 1x 1.8 meter USB-C cable, 1x Pana Pen 34 in box with 1 meter Type-C charging cable, 1x product manual
CERTIFICATIONS	
Certifications	UL (US+Canada), Energy Star, CB, CE (EMC+LVD+RoHS), FCC, CEC, CA65, UKCA, Energy Star ErP, WEEE, VESA Display HDR400, FreeSync Premium, RoHS, REACH, Windows Hello (camera), EMC